## newline



Elara is the eighth largest moon of Jupiter. And with a size of only 2% of Europe, the smallest of the four Galilean moons.



















## MOST VERSATILE HYBRID SOLUTION


As the more powerful sister of Lyra, Elara really steals the show. This high-end interactive display carries every experience you could want in your workspace; faster, enhanced sound, a superior touch and writing experience due to optical bonding, a modular camera and built-in microphone making Elara a true hybrid solution. The extra wide viewing angle ensures everyone in the room can benefit from the crystalclear 4K image and vibrant colours. Elara has it all!



## **NEWLINE INTERACTIVE ECOSYSTEM**

The completely renewed Interactive Ecosystem is full of software that helps you use your interactive display to the max. Whether it's setting up your video conference super fast, using concept mapping to brainstorm, connecting your device, sharing your screen or broadcasting!













MODEL		FRONT I/O	
Elara 65"	TT-6522Q	USB Type-C (Powered 100 W)	1
Elara 75"	TT-7522Q	HDMI IN 2.0	1
Elara 86"	TT-8622Q	USB Type-B (Touch)	1
		USB 3.0 Type-A	1
PANEL		Microphone In	1
Backlight	Direct LED ( Wide color gamut +		
Buokingine	Anti blue light)	REAR I/O	
Glass Surface	Anti-Glare+Anti-Fingerprint,	HDMI IN 2.0	2
	+ Antimicrobial Tempered Glass	DisplayPort 1.2	1
Bonding Technology	Certified Optical Bonding	USB Type-B (Touch)	3
Disulan Anas	65": 1428 x 803 mm	USB 3.0 Type-C	1
Display Area	75": 1650 x 928 mm 86": 1895 x 1066 mm	(Powered 15W)	
Diaplay Patio	16:09	USB 3.0 Type-A	2
Display Ratio Resolution		USB 3.0 Type-A to Android	1
Colours	3840 x 2160 (4K) 1,07 Billion	HDMI OUT 2.0	1
	400 cd/m <sup>2</sup>	RS232	1
Brightness Contrast Ratio	5000:1	RJ45 (Gigabit)	In x 1 / Out x 1
		OPS Slot	
Response Time Viewing Angle	6 ms 178°	SPDIF	1
Display Life Time	≥50000 hours	Audio Line Out	1
Transparency	>88%	WIFI Module Slot	1
Haze	2 %~5%	SDM-S Slot	
Touch Surface Hardness	7H	Power Out Connect (180 W)	1
Touch Surface Hardness	711	NFC	1
DOWER CONSUMPTION			
POWER CONSUMPTION	65": 133 W	SMART SYSTEM	A
Standard mode	75": 150 W	CaC Chinash	Amlogic A311D2 octa-core
otariadia mode	86": 168 W	SoC Chipset	processor 4 x Cortex-A73 at 2,2 Ghz, 4 x Corte x-A53 at 2,0 Ghz
Standby Mode	<0,5 W	RAM	8 GB (DDR4)
etanasy meas	10,0 11	Storage	128 GB
TOUCH			Android 11(Upcoming OTA
Touch Technology	Stellar Touch Technology	Operating System	Android 13 Upgrade)
Touch Points	40 Windows / 20 Android	Formats Support For Image	JPEG, BMP, PNG
Touch Screen Writing Tools	Passive pen, Finger, Fist	Torridia oupport For image	MPEG1, MPEG2, MPEG4, Sore
Number of stylus	2		nsonH.263,H.263,H.264,MVC,
Accuracy	±1 mm	Formats Support For Video	AVS,AVS+,WMV3,VC1,Motion
,			JPEG,VP8,VP9,RV30/RV40
SPEAKER			MPEG1/2 @LAYER1; @LAYER2;
Speaker Position	Front Facing		@LAYER3, EAC3, ACC-LC,
Speaker Rated Impedance	6 Ω	Formats Support For Audio	HEAAC, VORBIS, LPCM, IMA-
Speaker Freq.Response	250 Hz-20 KHz SPL -10 dB		ADPCM,MS-ADPCM,G711 A/MU-
Output S.P.L.	80±3 dB	Donatina ita C	LAW,LBR(COOK),FLAC
Speaker Max.Power Output	20 W x 2	Proximity Sensor	2
,		Camera	]
SUBWOOFER		Wi-Fi 6 + Bluetooth 5.2 Module	Integrated (Replaceable)
Speaker Position	Rear side		
Speaker Rated Impedance	4 Ω	EXTRA FIRMWARE FEATURES	
Speaker Freq.Response	20 Hz-20 KHz SPL -10 dB	Lan control	√
Output S.P.L.	77±2 dB	Wake on Lan	<b>√</b>
Speaker Max.Power Output	15 W x 1	CEC	1 Advaire to Edda and
,		Multiuser profile / User Profiles: 6	
MICROPHONE		Setting Menu Admin Mode	✓
Mic Possition	8 Microphone Array Upper Front	TD ANODODTATION / CTCC / CT	
Pick Up Distance	8 m	TRANSPORTATION / STORAGE	CF#. 1F10 y 00C y 11C
·	Echo cancellation, Beamforming,	Outline Dimensions	65": 1513 x 926 x 116 mm 75": 1735 x 1050 x 116 mm
Mic Performance	Noise Reduction	(Excl. wall mount)	86": 1981 x 1190 x 116 mm
			65": 39 Kg
		NI-+ NA/-1I-+	9
CAMERA MODULE			( p., pl   k u
	4K	Net Weight	75": 50 Kg 86": 65 Kg
CAMERA MODULE Camera Resolution Field of View	4K 120° FOV Lenses	Net weight	86": 65 Kg
			86": 65 Kg 65": 600 x 400 mm
Camera Resolution Field of View	120° FOV Lenses	VESA	86": 65 Kg

